



Technical features:

- Steel case and striker, painted aluminium grey
- Dead-locking latch
- 12 V ac CE
- Rated current 2,5A

Supplied as standard:

- Striker
- 3 keys item 1.01070.10.1
- Fixing screws
- Instruction sheet


Standards:

- This electric lock series is certified according to the European standard EN 14846:06:
 - Security degree 3 (500 Kg lateral thrust and 200 Kg front load)

Hand:

- 1 = R.H. inwards
- 2 = L.H. inwards
- 3 = R.H. outwards
- 4 = L.H. outwards

Type	Description	Cylinder	Throws	Backset	Unit weight 	Pieces 	ITEM			
							Type	Dim.	Hand	Fin.



• Inside push-button




1 02500 00 0

50	1,435	1	1	11610 50 1
50	1,440	1	1	11610 50 2
60	1,435	1	1	11610 60 1
60	1,445	1	1	11610 60 2
70	1,440	1	1	11610 70 1
70	1,450	1	1	11610 70 2
80	1,440	1	1	11610 80 1
80	1,440	1	1	11610 80 2



1 02552 50 0

50	1,445	1	1	11611 50 1
50	1,434	1	1	11611 50 2
60	1,440	1	1	11611 60 1
60	1,440	1	1	11611 60 2
70	1,445	1	1	11611 70 1
70	1,440	1	1	11611 70 2
80	1,439	1	1	11611 80 1
80	1,444	1	1	11611 80 2



• Inside push-button and cylinder
• Hold-open device










1 02104 00 0

50	1,538	1	1	11630 50 1
50	1,523	1	1	11630 50 2
60	1,533	1	1	11630 60 1
60	1,529	1	1	11630 60 2
70	1,500	1	1	11630 70 1
70	1,527	1	1	11630 70 2
80	1,536	1	1	11630 80 1
80	1,531	1	1	11630 80 2



1 02552 50 0

50	1,538	1	1	11631 50 1
50	1,538	1	1	11631 50 2
60	1,538	1	1	11631 60 1
60	1,538	1	1	11631 60 2
70	1,538	1	1	11631 70 1
70	1,538	1	1	11631 70 2

Type	Description	Cylinder	Throws	Backset	Kg	Unit weight	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.
 <ul style="list-style-type: none"> • Manual throw dead-bolt • Inside push-button and cylinder 	 <p>1 02146 00 0</p>	2 50 1,656 1 1 11670 50 1	2 50 1,650 1 1 11670 50 2	2 60 1,660 1 1 11670 60 1	2 60 1,670 1 1 11670 60 2	2 70 1,670 1 1 11670 70 1	2 70 1,665 1 1 11670 70 2	2 80 1,675 1 1 11670 80 1	2 80 1,675 1 1 11670 80 2			
		 <p>1 02145 00 1</p>	2 50 1,657 1 1 11671 50 1	2 50 1,654 1 1 11671 50 2	2 60 1,667 1 1 11671 60 1	2 60 1,666 1 1 11671 60 2	2 70 1,664 1 1 11671 70 1	2 70 1,670 1 1 11671 70 2	2 80 1,678 1 1 11671 80 1	2 80 1,679 1 1 11671 80 2		
			 <ul style="list-style-type: none"> • FOR OUTWARD OPENING DOORS • Inside push-button 	 <p>1 02500 00 0</p>	50 1,490 1 1 11610 50 3	50 1,490 1 1 11610 50 4	60 1,494 1 1 11610 60 3	60 1,495 1 1 11610 60 4	70 1,496 1 1 11610 70 3	70 1,486 1 1 11610 70 4	80 1,492 1 1 11610 80 3	80 1,480 1 1 11610 80 4
					 <ul style="list-style-type: none"> • FOR OUTWARD OPENING DOORS • Inside push-button and cylinder • Hold-open device 	 <p>1 02104 00 0</p>	50 1,523 1 1 11630 50 3	50 1,523 1 1 11630 50 4	60 1,529 1 1 11630 60 3	60 1,529 1 1 11630 60 4		